

2M IP Indoor IR Plastic Dome


NVP3-12-R

Features

- 2MP Small-sized Camera
- Maximum resolution 1920 (horizontal) X 1080 (vertical) / 30fps
- Horizontal angle of view 84 degrees (4.0mm) / Fixed lens option
- Day & Night(ICR)/IR visibility distance 15 meters
- Backlight compensation (D-WDR)
- PoE IEEE 802.3af/Class3



Dimension (mm)



Specification

Video	
Image Sensor	1/2.9" 2.2M CMOS
Channels	1
Total Pixel	2001(H) X 1121(V)
Max Resolution	1920(H) X 1080(V)
MIN. Illumination	0.25Lux, 0Lux with IR (F2.0)
Only installer Video Output	No
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens	
Focal Length	4.0mm
Aperture	F2.0
Lens Type	Fixed
IRIS Type	Auto Exposure
Horizontal Angle	D : 98°, H : 84°, V : 46°
Pan / Tilt / Zoom	Zoom :Fixed

Operational	
Shutter Speed	Auto / Manual (1/15 ~ 1/32000) Anti-Flicker Slow Shutter(1/2,1/3,1/5,1/6,1/7.5, 1/10)
Auto Gain Control (AGC)	Auto
Day & Night	TDN (True Day & Night)
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	D-WDR
Dynamic Range	No
LEDs	8IR
LED Distance	50ft(15m)
Privacy Zone	Yes
Function	Motion-Detection Mirror&Flip

Intelligent Video Analytic	
AI Intelligent Video Analytic	No

Encoder (video & audio)	
Video Compression	H.264 H.265 MJPEG

Encoder (video & audio)

Support Resolution	H.265 : 1920x1080/1280x720/352x288/352x240 H.264 : 1920x1080/1280x720/352x288/352x240 MJPEG : 1920x1080/1280x720/352x288/352x240
Intelligent Codec	Yes
Multiple Profile Streaming Performance	Triple Streaming(3rd Only MJPEG)
Video BitRate	100Kbps~10Mbps
Bitrate Control	Multi Streaming CBR/VBR at H.264,H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	No
Special Feature	Dynamic ROI(Region of Interest)

I/O & Event

Audio In / Out	No
Alarm In / Out	No
Mic	No
Event Trigger	Motion Alarm Temperature Critical Illegal Login Schedule
Event Notification	FTP E-Mail

Network

Ethernet	RJ45 (10/100Base-T)
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP ONVIF
Security	HTTPS(SSL) IP filtering 802.1x Digest Authentication
Application Programming I/F	CGI API ONVIF
Web viewer	MS Edge® Google Chrome®
Video management software (VMS)	Yes
Support languages	English Korean Japanese
Edge storage	No
SD Card Socket	No

Electrical

Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3af Class3
Power consumption	DC Max: 3.8W PoE Max: 5.5W

Environmental

Operating Temperature	-20°C ~ 50°C
Cold Start	No

Environmental	
Operating Humidity	10-90% RH(Non-Condensing)
Vandal Proof Casing	No
IP Rating	No
Other Certification	FCC CE ROHS KC

Mechanical	
Housing Model	VP3
Housing	Indoor Dome
Material	Plastic
Color	White
Dimensions (W x D x H)	105mm 74.6mm
Weight	0.21kg

Compatible Accessories



BW06
Wall Bracket



GP02
Gang Bracket