

4M IP MFZ IR Vandal Dome



NNK6-44-RS

Features

- 4MP camera
- 1/1.8" high sensitivity sensor
- Maximum resolution 2688 (horizontal) X 1520 (vertical) / 30fps
- Horizontal angle of view 90.5 degrees (wide angle) to 45.1 degrees (zoom) / Optical 2.7x
- Day & Night (ICR) / IR reach distance 21 meters
- Backlight compensation (WDR)
- SD/SDHC/SDXC memory slot
- PoE IEEE 802.3af/Class3
- IP67/IK10



Dimension (mm)



Specification

Video

Image Sensor	1/1.8" 4.53M CMOS
Total Pixel	2781(H) X 1632(V)
Max Resolution	2688(H) X 1520(V)
MIN. Illumination	0.024Lux 0Lux with IR (F1.5)
Only installer Video Output	1 [CVBS 1.0V p-p (75Ω)]
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens

Focal Length	3.6-10mm
Aperture	F1.5
Lens Type	Motorized_Varifocal
IRIS Type	P-IRIS
Horizontal Angle	D:51.5°~104.6°, H:45.1°~90.5°, V:25.3°~54.3°
Pan / Tilt / Zoom	Pan: Tilt : Zoom :X2.7 Optical

Operational

Shutter Speed	Auto / Manual (1/15 ~ 1/32000) Anti-Flicker Slow Shutter(1/2,1/3,1/5,1/6,1/7.5, 1/10)
Auto Gain Control (AGC)	Auto
Day & Night	TDN (True Day & Night)
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	WDR(2x)
Dynamic Range	120dB or above
LEDs	H2IR
LED Distance	70ft(22m)
Privacy Zone	Yes
Function	Motion-Detection Mirror&Flip

Intelligent Video Analytic

AI Intelligent Video Analytic	No
-------------------------------	----

Encoder (video & audio)

Video Compression	H.264 H.265 MJPEG
Support Resolution	H.265 : 2688x1520/2304x1296/1920x1080/1280x720/704x480/640x480/352x288/352x240 H.264 : 2688x1520/2304x1296/1920x1080/1280x720/704x480/640x480/352x288/352x240 MJPEG : 1920x1080/1280x720/800x600/768x432/704x576/704x480/640x480/352x288/352x240
Intelligent Codec	Yes
Multiple Profile Streaming Performance	Triple Streaming(3rd Only MJPEG)
Video BitRate	100Kbps~10Mbps
Bitrate Control	Multi Streaming CBR/VBR at H.264,H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	G.711 ulaw
Special Feature	Dynamic ROI(Region of Interest)

I/O & Event

Audio In / Out	1 Line Input[1.0Vrms, 3K ohm]/1 Line Output
Alarm In / Out	1 Line/1 Line
Mic	No
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule Sensor Detection
Event Notification	FTP E-Mail Alarm Out SD Card

Network

Ethernet	RJ45 (10/100Base-T)
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF
Security	HTTPS(SSL) IP filtering 802.1x Digest Authentication
Application Programming I/F	CGI API ONVIF
Web viewer	MS Edge® Google Chrome®
Video management software (VMS)	DW Spectrum® IPVMS
Support languages	English Korean Japanese
Edge storage	Micro SD Micro SDHC Micro SDXC
SD Card Socket	1

Electrical

Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3af Class3
Power consumption	DC Max: 11.3W PoE Max: 14.9W

Environmental

Operating Temperature	-20°C ~ 50°C
-----------------------	--------------









Environmental

Cold Start	-40°C
Operating Humidity	10-90% RH(Non-Condensing)
Vandal Proof Casing	IK10
IP Rating	IP68
Other Certification	FCC CE ROHS

Mechanical

Housing Model	NK6
Housing	Outdoor Dome
Material	Aluminum-Die Casting
Color	White
Dimensions (W x D x H)	139mm 125.4mm
Weight	1.25kg

Compatible Accessories

 <p>BC08 NPT</p>	 <p>BW08 Wall Bracket</p>	 <p>BR05 Inceiling Bracket</p>	 <p>BC08 Ceiling Bracket</p>
 <p>GP02 Gang Bracket</p>	 <p>BJC09 Wall Junction Bracket</p>	 <p>BP01 Pole Mount Bracket</p>	 <p>BCO01 Corner Mount Bracket</p>