

# AI 5M IP MFZ IR Bullet

NBT6-75L-RZ(550)

## Features




---

- 5MP AI Camera
- Supports Intelligent Video Analysis Events (Line/Intrusion/Queue Management)
- Maximum Resolution 2592 (Horizontal) X 1944 (Vertical) / 30fps
- Horizontal Field of View 46.2 degrees (Wide) ~ 7.7 degrees (Zoom) / 10x Optical Zoom
- Day & Night(ICR)/Night Vision up to 40 meters
- Backlight Compensation (WDR)
- SD/SDHC/SDXC Memory Slot
- PoE IEEE 802.3af/Class3
- IP67



## Dimension (mm)

---



## Specification

### Video

|                             |                                    |
|-----------------------------|------------------------------------|
| Image Sensor                | 1/2.8" 5.17M(STV2) CMOS            |
| Channels                    | 1                                  |
| Total Pixel                 | 2608(H) X 1984(V)                  |
| Max Resolution              | 2592(H) X 1944(V)                  |
| MIN. Illumination           | COLOR: 0.08Lux<br>BW: 0Lux with IR |
| Only installer Video Output | 1 [CVBS 1.0V p-p (75Ω)]            |
| S/N(signal/noise) Ratio     | 50dB                               |
| Scanning Mode               | Progressive Scan                   |

### Lens

|                   |  |
|-------------------|--|
| Focal Length      | 5~50mm                                   |
| Aperture          | F2.0                                     |
| Lens Type         | Motorized_Varifocal                      |
| IRIS Type         | P-IRIS                                   |
| Horizontal Angle  | D:9.6°~58.7°, H:7.7°~46.2°, V:5.7°~34.1° |
| Pan / Tilt / Zoom | Zoom :X10 Optical                        |

### Operational

|                          |   |
|--------------------------|---|
| Shutter Speed            | Auto / Manual (1/15 ~ 1/32000) Anti-Flicker Slow Shutter(1/2,1/3,1/5,1/6,1/7.5, 1/10) |
| Auto Gain Control (AGC)  | Auto  |
| Day & Night              | TDN (True Day & Night)  |
| Digital Noise Reduction  | 3D DNR  |
| Wide Dynamic Range (WDR) | WDR(2x)   |
| Dynamic Range            | 120dB or above  |
| LEDs                     | H3IR  |
| LED Distance             | 130ft(40m)  |
| Privacy Zone             | Yes   |
| Function                 | Motion-Detection LDC Mirror&Flip Auto White Balance                                   |

### Intelligent Video Analytic

|                               |   |
|-------------------------------|---|
| AI Intelligent Video Analytic | Yes   |
| Video analytics               | Intrusion Detection Zones&lines Tamper Detection Appear Filter Disappear Filter Dwell Filter Enter Filter Exit Filter Stopped Filter Counting Counting Lines Object Color Direction Filter Logical Rules Tailgating Filter DL People Tracker DL Object Tracker Metadata |

Encoder (video & audio)

|  |   |
|--|---|
| Video Compression                      | H.264 H.265 MJPEG   |
| Support Resolution                     | H.265 :<br>2592x1944/2560x1440/1920x1080/1280x720/800x600/704x576/704x480/640x480/640x360/352x288/352x240<br>H.264 :<br>2592x1944/2560x1440/1920x1080/1280x720/800x600/704x576/704x480/640x480/640x360/352x288/352x240<br>MJPEG :<br>1920x1080/1280x720/800x600/768x432/704x576/704x480/640x480/640x360/352x288/352x240 |
| Intelligent Codec                      | Yes   |
| Multiple Profile Streaming Performance | Triple Streaming(3rd Only MJPEG)  |
| Video BitRate                          | 100Kbps~25Mbps  |
| Bitrate Control                        | Multi Streaming CBR/VBR at H.264,H.265 (Controllable frame rate and Bandwidth)  |
| Video Bitrate extra comment            | Multi-rate for Preview and Recording  |
| Audio Compression                      | G.711 ulaw  |
| Special Feature                        | Dynamic ROI(Region of Interest)   |

I/O & Event

|                    |   |
|--------------------|---|
| Audio In / Out     | 1 Line Input[1.0Vrms, 3K ohm]/1 Line Output   |
| Alarm In / Out     | 1 Line/1 Line   |
| Mic                | No  |
| Event Trigger      | Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule Sensor Detection |
| Event Notification | FTP E-Mail Alarm Out SD Card  |

Network

|                             |  |
|-----------------------------|--|
| Ethernet                    | RJ45 (10/100Base-T)  |
| Protocol                    | TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF |
| Security                    | HTTPS(SSL) IP filtering 802.1x   |
| Application Programming I/F | CGI API ONVIF  |
| Web viewer                  | MS Edge® Google Chrome®  |
| Support languages           | English Korean Japanese  |
| Edge storage                | Micro SD Micro SDHC Micro SDXC   |
| SD Card Socket              | 1  |

Electrical

|                   |   |
|-------------------|---|
| Power Requirement | Adaptor is not included DC12V PoE IEEE 802.3af Class3 |
| Power consumption | DC Max: 8.8W PoE Max: 11.1W                           |

Environmental

|                       |                           |
|-----------------------|---------------------------|
| Operating Temperature | -20°C ~ 50°C              |
| Cold Start            | No                        |
| Operating Humidity    | 10-90% RH(Non-Condensing) |
| Vandal Proof Casing   | IK10                      |
| IP Rating             | IP67                      |
| Other Certification   | FCC CE ROHS UL            |

Mechanical

|                        |                      |
|------------------------|----------------------|
| Housing Model          | BT6                  |
| Housing                | Outdoor Bullet       |
| Material               | Aluminum-Die Casting |
| Color                  | White                |
| Dimensions (W x D x H) | 197.5mm<br>86mm      |
| Weight                 | 0.99kg               |

Compatible Accessories



**BJC12**

JUNCTION BRACKET



**BJC07**

Junction Bracket