

## CPRO-FN-5136ND

### Features

---

- \*\* 36ch HD-NVR \*\* HD-NVR With None PoE \*

Features : 36Ch Real Time Display and Real time Recording Throughput 200Mbps for 36Ch(Min. 2ea of HDD should be installed)  
ONVIF Compatible & Auto IP Camera Detection/Registration Dual(Main & Sub) Stream Recording/Display System Performance Monitoring (Bandwidth & Network Status, etc.) P2P Function that doesn't require Port Forwarding iSCSI function Support - External HDD through Network Smart Search - Multiple search by time & minutes' base Zero Configuration Supports H.264 & H.265 Supports

\* Specifications : Max HDD Bay/Min Installation : 4x SATA HDD / 2x SATA Video out : HDMI(Max UHD) & VGA Recording Speed : 1080fps Alarm Input/Relay Output : 16ch / 4ch LAN : 2EA Gigabit Ethernet(RJ45)-Fixed IP, DHCP & DDNS, DHCP server embedded Throughput (Bandwidth(Max)) : 200Mbps System operating Power : SMPS (110~240V AC) Max 145W Dimension(WxDxH) : 445 x 400 x 71 mm(~1.6U)



## Specification

---

Mechanical

Housing Model	none
---------------	------