CPRO
DIGITAL SURVEILLANCE SYSTEMS

4K IP MFZ IR Bubble Free Dome


NVD11-58-R

Features

- Weather Proof Design
- Water Proof Cable
- Two motor MFZ(Motorized Focus Controllable) / P-Iris lens
- Optimized Multiple Profile Streaming
- ROI(Region of Interest)
- Various Web Plug-in
- Smart AVC
- Advanced Built in ISP
- Double Scan Sensor with Advanced Built in ISP (8M)



Dimension (mm)



CPRO
DIGITAL SURVEILLANCE SYSTEMS

Specification

Video	
Image Sensor	1/2.8” 8.6M CMOS
Channels	1
Total Pixel	3864(H) X 2228(V)
Max Resolution	3840(H) X 2160(V)
MIN. Illumination	COLOR: 0.09Lux BW: 0Lux with IR
Only installer Video Output	1 [CVBS 1.0V p-p (75Ω)]
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens	
Focal Length	2.7~13.5mm
Aperture	F1.4
Lens Type	Motorized_Varifocal
IRIS Type	P-IRIS
Horizontal Angle	D:38.2°~105.0°, H:33.1°~90.3°, V:18.9°~49.0°
Pan / Tilt / Zoom	Zoom :X5 Optical

Operational	
Shutter Speed	Auto / Manual (1/15 ~ 1/32000) Anti-Flicker Slow Shutter(1/2,1/3,1/5,1/6,1/7.5, 1/10)
Day & Night	TDN (True Day & Night)
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	WDR(2x)
Dynamic Range	120dB or above
LEDs	H2IR
LED Distance	80ft(25m)
Privacy Zone	Yes
Function	Motion-Detection Mirror&Flip

Intelligent Video Analytic	
AI Intelligent Video Analytic	No

Encoder (video & audio)	
Video Compression	H.264 H.265 MJPEG

CPRO
DIGITAL SURVEILLANCE SYSTEMS

Encoder (video & audio)	
Support Resolution	H.265 : 3840x2160/2560x1440/1920x1080/1280x720/640x480/640x360/352x288/352x240 H.264 : 3840x2160/2560x1440/1920x1080/1280x720/640x480/640x360/352x288/352x240 MJPEG : 1920x1080/1280x720/800x600/768x432/704x576/704x480/640x480/640x360/352x288/352x240
Intelligent Codec	Yes
Multiple Profile Streaming Performance	Triple Streaming(3rd Only MJPEG)
Video BitRate	100Kbps~25Mbps
Bitrate Control	Multi Streaming CBR/VBR at H.264,H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	G.711 ulaw
Special Feature	Dynamic ROI(Region of Interest)

I/O & Event	
Audio In / Out	1 Line Input[1.0Vrms, 3K ohm]/1 Line Output
Alarm In / Out	1 Line/1 Line
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule Sensor Detection
Event Notification	FTP E-Mail Alarm Out SD Card

Network	
Ethernet	RJ45(1000Base-T(1Gbps))
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF
Security	HTTPS(SSL) IP filtering 802.1x
Application Programming I/F	CGI API ONVIF
Web viewer	MS Edge® Google Chrome®
Video management software (VMS)	Yes
Support languages	English Korean Japanese
Edge storage	Micro SD Micro SDHC Micro SDXC
SD Card Socket	1

Electrical	
Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3af Class3
Power consumption	DC Max: 12.4W PoE Max: 14.9W

Environmental	
Operating Temperature	-20℃ ~ 50℃
Operating Humidity	10-90% RH(Non-Condensing)

CPRO
DIGITAL SURVEILLANCE SYSTEMS

Environmental	
Vandal Proof Casing	IK09
IP Rating	IP66
Other Certification	FCC CE ROHS

Mechanical	
Housing Model	VD11
Housing	Outdoor Turret
Material	Aluminum-Die Casting
Color	White
Dimensions (W x D x H)	125mm 112mm
Weight	1kg

Compatible Accessories



BJC11
JUNCTION BRACKET



BC10 NPT



GP02
Gang Bracket




BJC03
Junction Bracket



BW10
Wall Bracket



BC10
Ceiling Bracket



BJC09
Wall Junction Bracket



BP01
Pole Mount Bracket

CPRO
DIGITAL SURVEILLANCE SYSTEMS



BCO01

Corner Mount Bracket