CPRO
DIGITAL SURVEILLANCE SYSTEMS

2M IP IR Mini Dome


NVD7-22-R

Features

- 2MP miniature camera
- Maximum resolution 1920 (horizontal) X 1080 (vertical) / 30fps
- Horizontal field of view 111 degrees (2.8mm), 86 degrees (4.0mm), 55 degrees (6.0mm), 40 degrees (8.0mm) / Fixed lens selection
- Day & Night (ICR) / IR visibility distance 19 meters
- Backlight compensation (WDR)
- SD/SDHC/SDXC memory slot
- PoE IEEE 802.3af/Class3
- IP67/IK10



Dimension (mm)



CPRO
DIGITAL SURVEILLANCE SYSTEMS

Specification

Video	
Image Sensor	1/2.8” 2.1M CMOS
Channels	1
Total Pixel	1945(H) X 1109(V)
Max Resolution	1920(H) X 1080(V)
MIN. Illumination	2.8mm : 0.05Lux, 0Lux with IR(F2.0) | 4mm : 0.09Lux, 0Lux with IR (F2.6) mm : 0.05Lux, 0Lux with IR (F2.0) | 8mm : 0.03Lux, 0Lux with IR (F1.6)
Only installer Video Output	No
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens	
Focal Length	2.8mm 4.0mm 6.0mm 8.0mm
Aperture	2.8mm, F2.0 | 4.0mm, F2.6 | 6.0mm, F2.0 | 8.0mm, F1.6
Lens Type	Fixed
IRIS Type	Auto Exposure
Horizontal Angle	D:128°, H:111°, V:62° (2.8mm) D:120°, H:86°, V:46° (4mm) D:64°, H:55°, V:30° (6mm) D:47°, H:40°, V:22° (8mm)
Pan / Tilt / Zoom	Zoom :Fixed

Operational	
Shutter Speed	Auto / Manual (1/15 ~ 1/32000) Anti-Flicker Slow Shutter(1/2,1/3,1/5,1/6,1/7.5, 1/10)
Auto Gain Control (AGC)	Auto
Day & Night	TDN (True Day & Night)
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	WDR(2x)
Dynamic Range	120dB or above
LEDs	H2IR
LED Distance	60ft(18m)
Privacy Zone	Yes
Function	Motion-Detection Mirror&Flip

Intelligent Video Analytic	
AI Intelligent Video Analytic	No

CPRO
DIGITAL SURVEILLANCE SYSTEMS

Encoder (video & audio)	
Video Compression	H.264 H.265 MJPEG
Support Resolution	H.265 : 1920x1080/1280x720/704x576/704x480/640x480/352x288/352x240 H.264 : 1920x1080/1280x720/704x576/704x480/640x480/352x288/352x240 MJPEG : 1920x1080/1280x720/800x600/768x432/704x576/704x480/640x480/640x360/352x288/352x240
Intelligent Codec	Yes
Multiple Profile Streaming Performance	Triple Streaming(3rd Only MJPEG)
Video BitRate	100Kbps~10Mbps
Bitrate Control	Multi Streaming CBR/VBR at H.264,H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	G.711 ulaw
Special Feature	Dynamic ROI(Region of Interest) Smart LBR

I/O & Event	
Audio In / Out	Mic / No
Alarm In / Out	No
Mic	Yes
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule
Event Notification	FTP E-Mail SD Card

Network	
Ethernet	RJ45 (10/100Base-T)
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF
Security	HTTPS(SSL) IP filtering 802.1x Digest Authentication
Application Programming I/F	CGI API ONVIF
Web viewer	MS Edge® Google Chrome®
Video management software (VMS)	Yes
Support languages	English Korean Japanese
Edge storage	Micro SD Micro SDHC Micro SDXC
SD Card Socket	1

Electrical	
Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3af Class2
Power consumption	DC Max: 3.7W PoE Max: 5.5W

Environmental	
Operating Temperature	-20℃ ~ 50℃

CPRO
DIGITAL SURVEILLANCE SYSTEMS

Environmental	
Cold Start	No
Operating Humidity	10-90% RH(Non-Condensing)
Vandal Proof Casing	IK10
IP Rating	IP67
Other Certification	FCC CE

Mechanical	
Housing Model	VD7
Housing	Outdoor Dome
Material	Aluminum-Die Casting
Color	White
Dimensions (W x D x H)	105mm 60.7mm
Weight	0.36kg

Compatible Accessories



BJC12
JUNCTION BRACKET



BC11 NPT



BJC04
Junction Bracket




BW11
Wall Bracket



BC11
Ceiling Bracket



GP02
Gang Bracket



BJC09
Wall Junction Bracket



BP01
Pole Mount Bracket

CPRO
DIGITAL SURVEILLANCE SYSTEMS



BCO01

Corner Mount Bracket