CPRO
DIGITAL SURVEILLANCE SYSTEMS

AI 5M IP MFZ IR Dome


NVD13-Z5-R

Features

- 5MP AI Camera
- Supports Intelligent Video Analysis Events
- Maximum Resolution 2592 (Horizontal) X 1944 (Vertical) / 30fps
- Horizontal Field of View 106 degrees (Wide-angle) ~ 35 degrees (Zoom) / Optical 4x Zoom
- Day & Night(ICR)/Night Vision up to 25 meters
- Backlight Compensation (WDR)
- SD/SDHC/SDXC Memory Slot
- PoE IEEE 802.3af/Class3
- IP67/IK10
- Built-in Microphone



Dimension (mm)



CPRO
DIGITAL SURVEILLANCE SYSTEMS

Specification

Video	
Image Sensor	1/2.4" 5.17M CMOS
Channels	1
Total Pixel	2608(H) X 1984(V)
Max Resolution	2592(H) X 1944(V)
MIN. Illumination	COLOR: 0.1Lux BW: 0Lux with IR
Only installer Video Output	No
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens	
Focal Length	2.8~12mm
Aperture	F1.6
Lens Type	Motorized_Varifocal
IRIS Type	P-IRIS
Horizontal Angle	D:41°~127°, H:35°~106°, V:20°~56°
Pan / Tilt / Zoom	Zoom :X4.2 Optical

Operational	
Shutter Speed	Auto / Manual (1/3 ~ 1/100,000)
Auto Gain Control (AGC)	Auto
Day & Night	TDN (True Day & Night)
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	WDR(2x)
Dynamic Range	120dB or above
LEDs	H2IR
LED Distance	80ft(25m)
Privacy Zone	Yes
Function	Motion-Detection Mirror&Flip Auto White Balance

Intelligent Video Analytic	
AI Intelligent Video Analytic	Yes

CPRO
DIGITAL SURVEILLANCE SYSTEMS

Encoder (video & audio)	
Video Compression	H.264 H.265 MJPEG
Support Resolution	H.265 : 2592x1944/2560x1440/1920x1080 H.264 : 2592x1944/2560x1440/1920x1080 MJPEG : 1920x1080/1280x720/800x600/768x432/704x576/704x480/640x480/640x360/352x288/352x240
Intelligent Codec	Yes
Multiple Profile Streaming Performance	Triple Streaming(3rd Only MJPEG)
Video BitRate	256Kbps~8Mbps
Bitrate Control	Multi Streaming CBR/VBR at H.264,H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	G.711 ulaw/AAC
Special Feature	Dynamic ROI(Region of Interest)

I/O & Event	
Audio In / Out	Mic /1 Line Output
Alarm In / Out	1 Line/1 Line
Mic	Yes
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule Sensor Detection
Event Notification	FTP E-Mail Alarm Out SD Card

Network	
Ethernet	RJ45 (10/100Base-T)
Protocol	TCP/IP ICMP HTTP/S FTP DHCP DNS DDNS RTP RTSP NTP UPnP SMTP IGMP 802.1X QoS IPv4/6 UDP Bonjour SSL/TLS PPPoE SNMP WebSocket/s SRTP SFTP ONVIFONVIF
Security	HTTPS(SSL) IP filtering 802.1x
Application Programming I/F	CGI API ONVIF
Web viewer	MS Edge® Google Chrome®
Support languages	English Korean Japanese
Edge storage	Micro SD Micro SDHC Micro SDXC
SD Card Socket	1

Electrical	
Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3af Class3
Power consumption	DC Max: 8.2W PoE Max: 9.5W

Environmental	
Operating Temperature	-30℃ ~ 50℃
Cold Start	No

CPRO
DIGITAL SURVEILLANCE SYSTEMS

Environmental	
Operating Humidity	10-90% RH(Non-Condensing)
Vandal Proof Casing	IK10
IP Rating	IP67
Other Certification	FCC CE ROHS

Mechanical	
Housing Model	VD13
Housing	Outdoor Dome
Material	Aluminum-Die Casting
Color	White
Dimensions (W x D x H)	125mm 92mm
Weight	0.52kg

Compatible Accessories



BR09
Inceiling Bracket



BJC11
JUNCTION BRACKET



BC10 NPT



GP02
Gang Bracket



BJC03
Junction Bracket



BW10
Wall Bracket



BC10
Ceiling Bracket



BJC09
Wall Junction Bracket

CPRO
DIGITAL SURVEILLANCE SYSTEMS



BP01

Pole Mount Bracket



BCO01

Corner Mount Bracket