CPRO
DIGITAL SURVEILLANCE SYSTEMS

AI 4K IP MFZ Full-Color Bullet


NBT20-98-WS

Features

- 4K AI Full-Color AI ISP Camera
- Supports Intelligent Video Analysis Events (Line Crossing/Intrusion/Queue Management..)
- 1/1.8" High-Sensitivity Sensor
- Maximum Resolution3840 (horizontal) X 2160 (vertical) / 30fps
- Horizontal Field of View 111 degrees (Wide) ~ 47 degrees (Zoom) / 3.7x Optical Zoom
- Full-Color(AI ISP) / White LED
- Backlight Compensation (HDR)
- SD/SDHC/SDXC Memory Slot
- SSD(M.2)
- PoE IEEE 802.3at/Class4
- IP67/IK10
- Built-in Microphone
- Built-in Junction Box
- Built-in Tamper Switch
- Built-in Anti-Condensation Heater



Dimension (mm)



CPRO
DIGITAL SURVEILLANCE SYSTEMS

Specification

Video	
Image Sensor	1/1.8” 8.48M(STV2) CMOS
Channels	1
Total Pixel	3856(H) X 2200(V)
Max Resolution	3840(H) X 2160(V)
MIN. Illumination	0.02Lux/0Lux with White
Only installer Video Output	1 [CVBS 1.0V p-p (75Ω)]
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens	
Focal Length	2.7~10mm
Aperture	F1.3
Lens Type	Motorized_Varifocal
IRIS Type	P-IRIS
Horizontal Angle	D:54°~129°, H:47°~111°, V:27°~57°
Pan / Tilt / Zoom	Zoom :3.7X Optical

Operational	
Shutter Speed	Auto / Manual (1/15 ~ 1/32000) Anti-Flicker Slow Shutter(1/2,1/3,1/5,1/6,1/7.5, 1/10)
Auto Gain Control (AGC)	Auto
Day & Night	No
Digital Noise Reduction	AI-ISP
Wide Dynamic Range (WDR)	HDR
Dynamic Range	120dB or above
LEDs	H4W
LED Distance	140ft(43m)
Privacy Zone	Yes
Function	Motion-Detection LDC Mirror&Flip Auto White Balance AI-ISP AI-HDR

Intelligent Video Analytic	
AI Intelligent Video Analytic	Yes
Video analytics	Intrusion Detection Zones&lines Tamper Detection Appear Filter Disappear Filter Dwell Filter Enter Filter Exit Filter Stopped Filter Counting Counting Lines Object Color Direction Filter Logical Rules Tailgating Filter DL People Tracker DL Object Tracker Metadata

CPRO
DIGITAL SURVEILLANCE SYSTEMS

Encoder (video & audio)	
Video Compression	H.264 H.265 MJPEG
Support Resolution	H.265 : 3840x2160/3200x1800/2560x1440/1920x1080 H.264 : 3840x2160/3200x1800/2560x1440/1920x1080 MJPEG : 1920x1080/1280x720/800x600/768x432/704x576/704x480/640x480/640x360/512x384/512x288
Intelligent Codec	Yes
Multiple Profile Streaming Performance	Triple Streaming(3rd Only MJPEG)
Video BitRate	100Kbps~25Mbps
Bitrate Control	Multi Streaming CBR/VBR at H.264,H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	G.711 ulaw
Special Feature	Dynamic ROI(Region of Interest)

I/O & Event	
Audio In / Out	Choose MIC or 1 Line Input[1.0Vrms, 3K ohm] / 1 Line Output & Speaker
Alarm In / Out	1 Line/1 Line
Mic	Yes
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule Sensor Detection
Event Notification	FTP E-Mail Alarm Out SD Card

Network	
Ethernet	RJ45(1000Base-T(1Gbps))
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF
Security	HTTPS(SSL) IP filtering 802.1x
Application Programming I/F	CGI API ONVIF
Web viewer	MS Edge® Google Chrome®
Support languages	English Korean Japanese Vietnamese
Edge storage	Micro SD Micro SDHC Micro SDXC M.2(SSD)
SD Card Socket	1

Electrical	
Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3at Class4
Power consumption	DC Max: 24.0W PoE Max: 27.5W

Environmental	
Operating Temperature	-40℃ ~ 50℃
Cold Start	No

CPRO
DIGITAL SURVEILLANCE SYSTEMS

Environmental	
Operating Humidity	10-90% RH(Non-Condensing)
Vandal Proof Casing	IK10
IP Rating	IP67
Other Certification	FCC CE ROHS

Mechanical	
Housing Model	BT20
Housing	Outdoor Bullet
Material	Aluminum-Die Casting
Color	White
Dimensions (W x D x H)	140mm 289mm
Weight	2.4kg