CPRO
DIGITAL SURVEILLANCE SYSTEMS

AI 5M IP MFZ IR Turret Dome


NVD3-E5L-R

Features



- 5MP AI Camera
- Supports Intelligent Video Analysis Events (Intrusion, Dwell, Counting Line)
- Maximum Resolution 2592 (H) X 1944 (V) / 30fps
- Horizontal Field of View 84 degrees (Wide) ~ 22 degrees (Zoom) / 4.4x Optical Zoom
- Day & Night(ICR)/IR Visibility up to 31 meters
- Backlight Compensation (WDR)
- SD/SDHC/SDXC Memory Slot
- PoE IEEE 802.3af/Class3
- IP67/IK10
- Built-in Microphone

Dimension (mm)



CPRO
DIGITAL SURVEILLANCE SYSTEMS

Specification

Video	
Image Sensor	1/2.8” 5.17M(STV2) CMOS
Channels	1
Total Pixel	2608(H) X 1984(V)
Max Resolution	2592(H) X 1944(V)
MIN. Illumination	COLOR: 0.04Lux BW: 0Lux with IR
Only installer Video Output	No
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens	
Focal Length	3.3~14.5mm
Aperture	F1.4
Lens Type	Motorized_Varifocal
IRIS Type	Auto Exposure
Horizontal Angle	D:28°~107°, H:22°~84°, V:17°~61°
Pan / Tilt / Zoom	Zoom :4.4X Optical

Operational	
Shutter Speed	Auto / Manual (1/15 ~ 1/32000) Anti-Flicker Slow Shutter(1/2,1/3,1/5,1/6,1/7.5, 1/10)
Auto Gain Control (AGC)	Auto
Day & Night	TDN (True Day & Night)
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	WDR(2x)
Dynamic Range	120dB or above
LEDs	H2IR
LED Distance	100ft(31m)
Privacy Zone	Yes
Function	Motion-Detection Mirror&Flip Auto White Balance

Intelligent Video Analytic	
AI Intelligent Video Analytic	Yes
Video analytics	Intrusion Detection Dwell Filter Counting Lines Metadata

CPRO
DIGITAL SURVEILLANCE SYSTEMS

Encoder (video & audio)	
Video Compression	H.264 H.265 MJPEG
Support Resolution	H.265 : 2592x1944/2560x1440/1920x1080/1280x720/704x480/640x480/640x360/352x240 H.264 : 2592x1944/2560x1440/1920x1080/1280x720/704x480/640x480/640x360/352x240 MJPEG : 1280x720/768x432/704x480/640x480/640x360/352x240
Intelligent Codec	Yes
Multiple Profile Streaming Performance	Triple Streaming(3rd Only MJPEG)
Video BitRate	100Kbps~25Mbps
Bitrate Control	Multi Streaming CBR/VBR at H.264,H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	G.711 ulaw
Special Feature	Dynamic ROI(Region of Interest)

I/O & Event	
Audio In / Out	Mic /1 Line Output
Alarm In / Out	1 Line/1 Line
Mic	Yes
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule Sensor Detection
Event Notification	FTP E-Mail Alarm Out SD Card

Network	
Ethernet	RJ45 (10/100Base-T)
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF
Security	HTTPS(SSL) IP filtering 802.1x
Application Programming I/F	CGI API ONVIF
Web viewer	MS Edge® Google Chrome®
Support languages	English Korean Japanese Vietnamese
Edge storage	Micro SD Micro SDHC Micro SDXC
SD Card Socket	1

Electrical	
Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3af Class3
Power consumption	DC Max: 8.6W PoE Max: 12.2W

Environmental	
Operating Temperature	-30℃ ~ 60℃
Cold Start	No

CPRO
DIGITAL SURVEILLANCE SYSTEMS

Environmental	
Operating Humidity	10-90% RH(Non-Condensing)
Vandal Proof Casing	IK10
IP Rating	IP67
Other Certification	FCC CE ROHS

Mechanical	
Housing Model	VD3
Housing	Outdoor Dome
Material	Aluminum-Die Casting
Color	White
Dimensions (W x D x H)	125mm 121.7mm
Weight	0.85kg

Compatible Accessories



BJC11
JUNCTION BRACKET



BC10 NPT



GP02
Gang Bracket




BJC03
Junction Bracket



BW10
Wall Bracket



BC10
Ceiling Bracket



BJC09
Wall Junction Bracket



BP01
Pole Mount Bracket

CPRO
DIGITAL SURVEILLANCE SYSTEMS



BCO01

Corner Mount Bracket